■ Communication Performance

- 4G LTE, Global band
- 802.1 1ac/a/b/g/n enterprise level WI-FI
- Bluetooth 5.0, low power, long distance perfect matching wireless printer

■ I Industrial Protection

- IP65 industrial protection
- Optimized structure for battery to ensure slim form factor

Scanning Performance

- | New generation slim 2D imager scan engine
- Support megapixel versions
- | Licensed Datalogic decoding technology

■ Unique Product Characteristics

- | Quad Core processor, long life cycle
- Support Android 9 and Android 10 upgrades
- | Large battery capacity but refined power consumption, 3 hours charging time but 15 hours working duration, 25days standby duration
- Free to insatll APPLOCK, Easy Deploy and other system mangement software for efficient management and deployment
- Accurate Reading Ability, only decode barcode label that's close to the center of the aiming pattern, even when many labels are crowded





Performance Parameter

0.0	
OS	Android 9
CPU	2GHz, Quad/Octa Core, 12nm
MEMORY	2+16/3+32
Extend Slot	MicroSD, support SDHC, up to 64GB
	One micro SIM connector
PC Communication	USB 2.0 OTG; Type-C; Support Type-C Headset
Sensors	Light, Proximity, 3D G sensor, Hall, E-compass
LED	Charging, Scan and System status
Charging Time	3 hours
Operating Duration Data Collection	15 hours
Scan Engine	Mobydata E3200LE/E3250
2D	Aztec Code; China Han Xin Code; Data Matrix; MaxiCode
	Micro QR Code; QR Code; EAN/JAN Composites; GS1 DataBar Composites
	GS1 DataBar Expanded Stacked; GS1 DataBar Stacked
	GS1 DataBar Stacked Omnidirectional; MicroPDF417; PDF417
	Digimarc(only E3250);UPC A/E Composites
	Auto discriminates all standard 1D codes including GS1
1D	DataBar™ linear codes
Post	Australian Post; British Post; China Post; IMB; Japanese
	Post; KIX Post; Korea Post; Planet Code; Postnet; Royal
	Mail Code (RM4SCC)
NFC	13.56MHz NFC
Wireless Connectivity	
WLAN	802.11 ac/a/b/g/n
	TDD-LTE (B38/B39/B40/B41)
WWAN	FDD-LTE (B1/B3/B7/B8)
	UMTS/HSDPA/HSPA/HSPA+ (900/2100 MHz)
	GSM/EDGE/GPRS (900/1800MHz)
VoLTE	LTE CAT6
CA	Downlink 300Mbps, B1/B3/B7/B40/B41
WPAN	BT 5.0/BLE
GPS	GPS/A-GPS, GLONASS, Beidou, Galileo
Physical Specifications	
LCD	4.0 inch, 800*480, visible under sunshine
Touch	GFF Capacitive Touch
Camera	Auto focus 8Mega, with flash LED
Keypad	24 Numeric Keypad
	Left/Right Scan Key, Left/Right K1,K2 user-defined Key
	Back, Home, Switch
Receiver	Support
Speaker	Min 90db at 10cm-1KHz Voice
Mic	Noise Reduction Mic
Charging IO	USB Type-C
Charging 10	Charging Pad
Battery	Removable 4000mAh
Dimension	160mm×71mm×17mm
Weight	269g
Environmental Specifications	
Operating Temperature	-20°C ~ +50°C
Storage Temperature	-30°C ∼ +70°C
Humidity	10% ~ 90%
Drop	1.5m, concrete
Tumble	600hits, 0.5m, Steel
IP	IP65
ESD	±8kV Contact, ±15kV Air
Keypad lifecycle	300K
Accessories	
Charging Cradle	Support 1 device and 1 battery
Handstrap	Black, Nylon
Battery	Removable 4000mAh
Gift Box	
Device, Battery, QSG, Adapter, U	ISB cable.







